

Broadalighting, Inc.



Micro Spiral

120V 60Hz stock 2700K/5000K, other colors optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter Tube	Diameter Ballast	CRI	PFA	THD	Energy Star
BCS-9	Micro Spiral T2	9	40	550	10000	3.3H	1.1H/16	1.5B	84	High	Low	Yes
BCS-11	Micro Spiral T2	11	50	650	10000	3.13H/6	1.1H/16	1.5B	84	High	Low	Yes
BCS-14	Micro Spiral T2	14	60	820	10000	4.1H	1.1H/16	1.5B	84	High	Low	Yes



Mini Spiral

120V 60Hz stock 2700K/5000K, other colors optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter Ballast	CRI	PFA	THD	Energy Star
SMR-9	Mini Spiral T3	9	40	520	10000	4.1H	1.3H	84	High	Low	N/A
SMR-11	Mini Spiral T3	11	50	650	10000	4.1H	1.3H	84	High	Low	N/A
SMR-13	Mini Spiral T3	13	60	800	10000	4.3H	1.3H	84	High	Low	N/A
SMR-15	Mini Spiral T3	15	65	850	10000	5	1.3H	84	High	Low	Retired
BMS-15	Mini Spiral T3	15	65	850	10000	5	1.3H	84	High	Low	Retired
BMS-19	Mini Spiral T3	19	75	1200	10000	5.1H	1.7B	84	High	Low	N/A
BDS-20	Mini Spiral T3	20	75	1350	10000	5.1H	1.3H	84	High	Low	Yes
BDS-23	Mini Spiral T3	23	100	1690	10000	5.1H	1.7B	84	High	Low	Yes



FCC



148 S. 8th Avenue, Suite H, City of Industry, CA 91746
 Tel: 626.961.6661 • 626.968.1288 Fax: 626.961.6652
 info@broadalighting.com
 www.broadalighting.com

Broadalighting, Inc.



Super Spiral

120V 60Hz stock 5000K, other colors optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter Ballast	CRI	PFA	THD
SDR-45	Super Spiral T5	45	175	3300	8000	8	3 1/8	92	High	Low
SDR-55	Super Spiral T5	55	250	3500	8000	8 3/8	3 1/8	92	High	Low
SDR277-55	Super Spiral T5, 277V	55	250	3800	8000	5 3/8	3 1/8	92	High	Low
SDR-65	Super Spiral T5	65	300	4200	8000	8 3/8	3 1/8	92	High	Low
SDR-85	Mini Spiral T3	85	400	5500	8000	11	3 1/8	92	High	Low
SDR277-85	Mini Spiral T3, 277V	85	400	5500	8000	11	3 1/8	92	High	Low



FCC



148 S. 8th Avenue, Suite H, City of Industry, CA 91746
 Tel: 626.961.6661 • 626.968.1288 Fax: 626.961.6652
 info@broadalighting.com
 www.broadalighting.com

Broadalighting, Inc.



A Type

120V 60Hz stock 2700K/5000K, other colors optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter Ballast	CRI	PFA	THD	Energy Star
BAC-9	A19 Type T2	9	40	535	10000	4 1/3	1 3/4	84	High	Low	Yes
BAC-14	A19 Type T2	14	60	700	8000	4 1/2	1 3/4	84	High	Low	Yes
SGF-9	A19 Type T2	9	40	500	8000	5	2 5/8	82	High	Low	N/A
SGF-14	A19 Type T2	14	60	650	8000	5 3/8	2 5/8	82	High	Low	N/A



Reflector

120V 60Hz stock 2700K/5000K, other colors optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter	CRI	PFA	THD
SER-15FL	Par-30 Flood, Wet proof	15	60	690	8000	5 1/2	3 3/4	82	High	Low
SER-24FL	Par-36 Flood, Wet proof	24	90	1200	8000	6	5	82	High	Low
SER-15	R-30 Frost, Indoor	15	60	650	8000	5 5/8	3	82	High	Low
EBR-15	R-30 Clear, Indoor	15	60	650	8000	5 5/8	3	82	High	Low
SER-20	R-30 Frost, Indoor	20	75	800	8000	6 1/2	2 1/2	84	High	Low
SER-24	R-40 Frost, Indoor	24	90	1450	8000	7 1/4	5	84	High	Low



FCC



148 S. 8th Avenue, Suite H, City of Industry, CA 91746
 Tel: 626.961.6661 • 626.968.1288 Fax: 626.961.6652
 info@broadalighting.com
 www.broadalighting.com

Broadada, Inc.



Specialty

120V 60Hz stock 2700K/5000K, other colors optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter Ballast	CRI	PFA	THD
SGF-5C	Torpedo E12 Candle bra Base	5	20	300	8000	4 1/4	1 1/2	84	High	Low
SGF-5M	Torpedo E26 Medium Base	5	20	300	8000	4 1/4	1 1/2	84	High	Low
SGF-9C	Torpedo E12 Candle bra Base	9	30	500	8000	5 1/2	1 1/2	84	High	Low
STG-15	G-30 Globe	15	60	690	8000	6	4 1/2	84	High	Low
BLN-1	LED Night Light	0.3	5	70	100000	4	1 1/2	84	High	Low



GU-24 base CFL

120V 60Hz stock 2700K, other colors optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter Tube	Diameter Ballast	CRI	PFA	THD	Energy Star
BDS-18GU	Mini Spiral T3, GU-24 Base	18	75	1200	10000	4 1/4	2 3/8	2	84	High	Low	Yes
BDS-26GU	Mini Spiral T3, GU-24 Base	26	120	1750	10000	4 1/2	2 3/8	2	84	High	Low	N/A



FCC



148 S. 8th Avenue, Suite H, City of Industry, CA 91746
 Tel: 626.961.6661 • 626.968.1288 Fax: 626.961.6652
 info@broadalighting.com
 www.broadalighting.com

Broadalighting, Inc.



Dimmable Cold Cathode Fluorescent Lamp (CCFL)

120V 60Hz stock 2700K/5000K, other colors optional, all dimmable with regular dimming switch

Product code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter	CRI	PFA	THD
BCNC-5	A Type Clear, Dimmable	5	15	200	25000	4 1/2	2	85	>0.96	Low
BCNF-5	A Type Frost, Dimmable	5	15	200	25000	4 1/2	2	85	>0.96	Low
BCNC-8	A Type Clear, Dimmable	8	20	320	25000	5	2 3/8	85	>0.96	Low
BCNF-8	A Type Frost, Dimmable	8	20	320	25000	5	2 3/8	85	>0.96	Low
BCF-5M	Torpedo Frost E26 Base, Dimmable	5	15	200	25000	5 3/8	1 3/4	85	>0.96	Low
BCF-5C	Torpedo Frost E12 Base, Dimmable	5	15	200	25000	5 3/8	1 3/4	85	>0.96	Low
BCI-8	R-20 Reflector Frost, Dimmable	8	20	320	25000	4 3/4	2 1/2	85	>0.96	Low
BCR-8	R-30 Reflector Frost, Dimmable	8	20	320	25000	4 1/2	3	85	>0.96	Low
BCRP-8	R-30 Reflector Frost Pink Color, Dimmable	8	20	320	25000	4 1/2	3	85	>0.96	Low
BCBS-13	Bare Spiral, Dimmable	13	40	500	25000			85	>0.96	Low



FCC



148 S. 8th Avenue, Suite H, City of Industry, CA 91746
 Tel: 626.961.6661 • 626.968.1288 Fax: 626.961.6652
 info@broadalighting.com
 www.broadalighting.com

Broadada, Inc.



BSDM-15



BSDM-23



BDSER-15



BDSER-23



BACD-15



BSDM-15GU



BSDM-23GU

DIM-BRITE Dimmable CFL

120V 60Hz Stock 2700K/5000K, other color optional

Product Code	Description	Watt	Incand Watt	Lumens	Rated Life	Length	Diameter	CRI	PFA	THD
BSDM-15	Spiral T3 dimmable	15	65	1100-900	8000	4 3/4	2 3/8	82	0.98	Low
BSDM-23	Spiral T3 dimmable	23	100	1600-1300	8000	5 1/4	2 3/8	82	0.98	Low
BACD-15	A type T2 dimmable	15	60	900-750	8000	5 1/4	2 1/2	82	0.98	Low
BDSER-15	Reflector R-20 T2 dimmable	15	60	900-750	8000	5 1/4	2 5/8	82	0.98	Low
BDSER-23	Reflector R-30 T2 dimmable	23	75	1150-950	8000	5 7/16	3 3/4	82	0.98	Low
BSDM-15GU	Spiral T3 dimmable GU24	15	65	1100-900	8000	4 1/4	2 3/8	82	0.98	Low
BSDM-23GU	Spiral T3 dimmable GU24	23	100	1600-1300	8000	4 3/4	2 3/8	82	0.98	Low



FCC



148 S. 8th Avenue, Suite H, City of Industry, CA 91746

Tel: 626.961.6661 • 626.968.1288 Fax: 626.961.6652

info@broadalighting.com

www.broadalighting.com